

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Anadarko Production Co</u>		Lease <u>Bradshaw</u>		Well # <u>1</u>	
Location of Well	Unit <u>6605 P</u> <u>660E</u>	Section <u>4</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>Warton</u>		Type of Equipment <u>Rotary</u> <u>12/3/80</u>		
* Witness					
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48 #</u>		<u>400'</u>	<u>300 SX Circ</u>
* <u>12 1/4</u>	<u>8 5/8</u>	<u>24 #</u>		<u>1200'</u>	<u>800 SX Circ</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>11.6 #</u>		<u>9500'</u>	<u>350 SX</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required _____					
Type of Shoe used <u>Guide</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>Yes</u>					
TD of hole <u>1250</u> Set <u>1262</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>K-55</u>					
New-used csg. @ <u>1262</u> with <u>2000</u> sacks neat cement around shoe					
+ <u>.500</u> sax <u>Hawco Lite</u> additives _____					
Plug down @ <u>8:30</u> (AM) (PM) Date <u>1-31-81</u>					
Cement circulated <u>Yes</u> No. of Sacks <u>50</u>					
Cemented by <u>Hawco</u> Witnessed by <u>BLW</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Loss circulation @ 830 ft</u>					