

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>W. H. Petroleum Corp.</u>		Lease <u>South 1/4 Sec 14 T. 15 N. R. 24 E. S. 1</u>		Well # <u>2</u>	
Location of Well	Unit <u>Unit B</u>	Section <u>14</u>	Township <u>15</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor	<u>Captan</u>		Type of Equipment <u>Rotary</u>		
* Witness <u>1</u>					
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/4</u>	<u>23# J-55</u>		<u>1500'</u>	<u>5000</u>
<u>12 1/4</u>	<u>8 5/8</u>	<u>24# J-55</u>		<u>95'</u>	<u>500</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>10.5# J-55</u> <u>10.5# J-55</u>		<u>9000</u>	<u>5000</u>
Casing Data:					
Surface <u> </u> joints of <u> </u> inch <u> </u> # Grade <u> </u>					
(Approved) (Rejected) <u> </u>					
Inspected by <u> </u> date <u> </u>					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required <u> </u>					
Type of Shoe used <u>Guide</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>921</u> Set <u>933</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>J-55</u>					
New-used csg. @ <u>933</u> with <u>150</u> sacks neat cement around shoe					
+ <u>200</u> sy sax <u>C 3% CC</u> additives <u>+ 400</u> sy <u>65-35</u> Pps Mix					
Plug down @ <u>5100</u> () (PM) Date <u>1-15-81</u>					
Cement circulated <u>yes</u> No. of Sacks <u>80</u> sy					
Cemented by <u>Dowell</u> Witnessed by <u>BW Weaver</u>					
Temp. Survey ran @ <u> </u> (AM) (PM) Date <u> </u> top cement @ <u> </u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u>Last Drilling Break 810 ft</u>					