

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 100
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>Hagback "PO" st Com</u>		Well # <u>1</u>	
Location of Well	Unit <u>66N 1980W C</u>	Section <u>20</u>	Township <u>19</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor	<u>Moran #9 Rig</u>		Type of Equipment <u>Rotary 1-30-81</u>		
* Witness					
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 3/4"</u>	<u>48 #</u>		<u>312'</u> 350'	<u>250 SX-Circ</u>
<u>12 1/4"</u>	<u>8 5/8"</u>	<u>24 #</u>		<u>950'</u>	<u>450 SX Circ</u>
<u>7 7/8"</u>	<u>5 1/2" or 4 1/2"</u>	<u>15.5# - 17# or 10.5# - 11.6#</u>		<u>8800'</u>	<u>6</u>
Casing Data:					
Surface <u>23</u> joints of <u>8 5/8"</u> inch <u>24</u> # Grade <u>J-55</u>					
(Approved) (Rejected)					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>12 1/4"</u> Size of Casing <u>8 5/8"</u> Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>930'</u> Set <u>930'</u> Feet of <u>2"</u> Inch <u>24</u> # Grade <u>J-55</u>					
New-used csg. @ <u>930'</u> with <u>150 3/4cc</u> sacks neat cement around shoe					
+ <u>200</u> sax <u>C</u> additives <u>270cc</u>					
Plug down @ <u>9300'</u> (AM) (PM) Date _____					
Cement circulated <u>No</u> No. of Sacks - <u>0</u>					
Cemented by <u>Dowell</u> Witnessed by <u>Michael Stillfield</u>					
Temp. Survey ran @ <u>1300</u> (AM) (PM) Date <u>2/18/81</u> top cement @ <u>175'</u>					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>+800sx 6 3/4 sp. (8# Kolite, 4% gel, 1/4 celvoral, 3% cc)</u>					
No cent.					
last circ. @ 341'					
last dry break @ 600'					

1. Ran 1" Tagged To c @ 308'
Pumped 100sx C 470cc.
2. Ran 1" Tagged To c @ 276'
Pumped 100sx C 470cc.
Cement circulated to surface.