

+ c/sr
dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

AUG 31 '89

O. C. U.

WELL API NO.

30-015-23636

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

LG 3998

7. Lease Name or Unit Agreement Name

Hogback PO State Com

8. Well No.

1

9. Pool name or Wildcat

Undesignated

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER Recompletion

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line

Section 20 Township 19S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3764' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Plugback, perforate, treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-30-89. Rig up. POH. WIH w/packer and RBP. Found hole in casing between 3752' and 3900'. Set CIBP 5250'. Perforate 4 squeeze holes at 5216'. Set retainer 5196'. Cement 1st stage w/250 gal mud flush, 125 sx Lite and 75 sx Class C with fluid loss additives and 3# salt. Pull out of retainer. Pull to 3780'. Reversed down 8-5/8" casing up 2-3/8" tubing. POH. Stage 2 - WIH w/retainer and set at 3718'. Established circulation. Cemented w/500 gals mud flush, 550 sx Lite + 75 sx Class C w/3# salt and fluid loss additives in all cement. Pull out of retainer. Reversed down 4 1/2" casing. POOH. WOC. Drill squeeze. Cleaned out hole to 5250'.

8-16-89. Perforated 4802-4810' (8 holes) and 4826-4833' (7 holes) w/15 - .40" holes (1 SPF). Treated perfs 4802-4833' w/2000 gals 20% NEFE acid, N2 and ball sealers. Swabbed dry. Perforated 3925-4698' w/23 .40" holes as follows: 3925, 26, 3974, 77, 79, 4072, 74, 75, 77, 4502, 03, 04, 23, 24, 26, 4616, 23, 74, 76, 88, 89, 96, and 4698'. Treated perfs 3925-4698' w/5000 gals 20% NEFE acid and 25 ball sealers.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Production Supervisor

DATE 8-30-89

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

APPROVED BY

SUPERVISOR, DISTRICT II

TITLE

DATE

AUG 31 1989

CONDITIONS OF APPROVAL, IF ANY: