

Marbob Energy Corp.
 Gulf St. #1
 330 FSL 1980 FEL Sec. 36-19S-29E

From	To	Thickness in feet	Formation
0	3	3	Sand
3	80	77	Gyp, red bed
80	90	10	Gyp
90	125	35	Gyp, shale
125	280	155	Anhy, shale
280	345	65	Shale
345	890	545	Salt
890	980	90	Salt, potash
980	1005	25	Salt
1005	1030	25	Anhy, salt
1030	1230	200	Salt
1230	1400	170	Anhy.
1400	1425	25	Gray lime
1425	1445	20	Lime, anhy
1445	1450	5	Gray shale
1450	1475	25	Gray lime, shale
1475	1500	25	Broken anhy, red sandy shale
1500	1510	10	Broken anhy.
1510	1520	10	Broken any, red sandy shale
1520	1542	22	Anhy.
1542	1560	18	Sand
1560	1565	5	Hard lime
1565	1570	5	Sand
1570	1575	5	Anhy, lime
1575	1595	20	Sand, anhy.
1595	1640	45	Sand, dolo, anhy.
1640	1650	10	Dolo.
1650	1660	10	Sand, dolo.
1660	1690	30	Sand, dolo, anhy.
1690	1720	30	Dolo, anhy.
1720	1770	50	Sand, dolo.
1770	1780	10	Dolo.
1780	1790	10	Sand, dolo.
1790	1850	60	Dolo.
1850	1860	10	Dolo, sand
1860	1870	10	Dolo.
1870	1890	20	Dolo, sand
1890	1920	30	Dolo.
1920	1950	30	Dolo, sand
1950	1970	20	Dolo.
1970	1980	10	Dolo, sand
1980-	2020	40	Dolo, lime
2020	2040	20	Dolo, sand, lime
2040	2060	20	Dolo, sand
2060	2080	20	Dolo, sand, lime
2080	2100	20	Dolo, lime
2100	2140	40	Dolo, sand
2140	2160	20	Dolo, shale
2160	2480	320	Dolo, sand
2480	2740	260	Dolo.
2740	2770	30	Dolo, sand
2770	2960	190	Dolo.
2960	2980	20	Dolo, sand
2980	3115	135	Dolo.