NEW MEXICO OIL CONSERVATION COMMITMON DRAWER DD ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

	Derator Vates Petroleum Corp			Leese Bogart PS'				Well # .				
	Location of Well 1650E		it Section				ip	Range 24	County Eddy			
	Drilling Contractor Artesic Fishing To				6					HSHP		
	* Witness APPROVED CASING PROGRAM											
	Size of No	le S	Size of Casing		Weig! For		New or Used		Depth Sacks		Comen	
ĸ	9 1/z		י׳ ר		20#				1,120'	Circ 550 SX		
	61/4		4 '/z''		9.5*				3250		300 SX	
-	Casing Data	a :		l								
	Surfacejoints ofinch# Grade											
ļ	(Approved) (Rejected) Inspected by date Cementing Program Size of hole $\frac{g}{2}$ Size of Casing $\frac{7'}{2}$ Sacks cement required Type of Shoe used <u>Guide</u> Float collar used <u>Tweet</u> Btm 3 jts welded <u>Ves</u> TD of hole <u>1135</u> Set <u>1136</u> Feet of 7 Inch 20 = Grade <u>K-55</u> New-weed csg. @ <u>1136</u> with <u>150</u> sacks neat coment around shoe + <u>400</u> sax <u>b5-35</u> fis Mix additives Plug down @ <u>4:30</u> (AM) (PM) Date <u>2-21-81</u>											
Ī												
l												
ĺ												
Cement circulated us No. of Sacks 405ax												
	Cemented by Dowell Witnessed by BWW Temp. Survey ran @(AM) (PM) Datetop cement @ Casing test @(AM) (PM) Date										_	
ł												
ľ												
l	Method Used Witnessed by											
Checked for shut off @ (AM) (PM) Date												
h	lethod used		·			Witne	ssed	Бу			· · · · · · · · · · · · · · · · · · ·	
1	(emarks:	Las	T Dxil	ling	Break		7					
				/								
				<u></u>						÷•••••		
	** A chan an a state of the second			·····								

۲ ا s,