UNITED STATES	Budget Burea	RECEIVE
DEPARTMENT OF THE INTERIOR	NM - 0557729	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TR	IBE NAMER 2 19
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	O. C. D. ARTESIA, OFFIC
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Hanson Feder	
1. oil gas well well other	9. WELL NO.	
2. NAME OF OPERATOR	1 10. FIELD OR WILDCAT NAME	
Anadarko Production Company 3. ADDRESS OF OPERATOR	Wildcat Bone	
P. O. Box 67, Loco Hills, New Mexico 88255	11. SEC., T., R., M., OR BLK. A AREA	ND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	20 - 195 - 3	31E
below.) AT SURFACE: 1910'FSL&2250'FEL Sec.20,T195,R31E	12. COUNTY OR PARISH 13.	
AT TOP PROD. INTERVAL: Same	· · · · · · · · · · · · · · · · · · ·	ew Mexico
AT TOTAL DEPTH: Same	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF,	KDB, AND WD)
ALL	3452.0 GL	
REQUEST FOR APPROVAL TO: SUBSEQUENT BEPORT OF SUBSEQUENT		
FRACTURE TREAT		
SHOOT OR ACIDIZE	1 1982 纪	
	(NOTE: Report results of multiple change on Form 9-330.)	completion or zone
MULTIPLE COMPLETE	& GAS CURVEY	
CHANGE ZONES	NEW MEXICO	
	NEW MEXICO	
ABANDON•	NEW MEXICO	pertinent dates
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine CTP f are (2,9300) KB (to	REW MEXICO REW MEXICO is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I	pertinent dates, ce locations and Lime).
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I at below Bone Springs S	pertinent dates, ce locations and Lime). Sand)
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (jus Ran RTTS pkr and established pump-in rate of 2 I	te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I at below Bone Springs S BPM @ 4500#. Set Hallin 025* ARAP = 2 BPM @ 45	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#.
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (just Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (00°) squeeze holes @ 8780' KB & Holes Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (00°) squeeze holes @ 8780' KB & Holes Ran RTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (00°) squeeze holes @ 8780' KB & Holes	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I ast below Bone Springs S BPM @ 4500#. Set Hallil 025°; AR&P = 2 BPM @ 4 alliburton cemented w/2	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#.
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (just Ran RTTS pkr and established pump-in rate of 2 1 retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I ast below Bone Springs S BPM @ 4500#. Set Hallil 025'; AR&P = 2 BPM @ 4 alliburton cemented w/2 alliburton cemented w/2	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#. LOO sx Class
ABANDON [•] (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (just Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 17. CFR & .3 of 17. Halad 22-A and 50 as	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I as below Bone Springs S BPM @ 4500#. Set Hallil 025'; AR&P = 2 BPM @ 4 alliburton cemented w/2 k w/.3 of 1% CFR-2.	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#. 100 sx Class rc to surface
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (jus Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 so Spotted 250 gals 15% acid; broke @ 5500# & immed	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I ab below Bone Springs S BPM @ 4500#. Set Hallil 025'; AR&P = 2 BPM @ 4 alliburton cemented w/2 k w/.3 of 1% CFR-2. diately established ci %. Set cement retaine	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#. 100 sx Class rc to surface r @ 8728 ^t &
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (just Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 ss Spotted 250 gals 15% acid; broke @ 5500# & immediate csg. ARAP = 3.5 BPM @ 4100	te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I at below Bone Springs S BPM @ 4500#. Set Hallin 025'; AR&P = 2 BPM @ 4 alliburton cemented w/2 k w/.3 of 1% CFR-2. diately established cir #. Set cement retaine bed 250 gals 15% acid	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#. 100 sx Class rc to surface r @ 8728' & with 500 gals
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (jus Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ho H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 so Spotted 250 gals 15% acid; broke @ 5500# & immediate csg. ABANDON* Halldburton Lifes	te all pertinent details, and give directionally drilled, give subsurfa abandon Bone Springs I abandon Bone Springs I at below Bone Springs S BPM @ 4500#. Set Hallin 025'; AR&P = 2 BPM @ 4 alliburton cemented w/2 k w/.3 of 1% CFR-2. diately established ci %. Set cement retaine ped 250 gals 15% acid to w/.3 of 1% CFR-23 o	pertinent dates, ice locations and Lime). Sand) Surton cement 500#. LOO sx Class rc to surface r @ 8728' & with 500 gals f 1% Halad 22
ABANDON [•] (other) X Ab _a ndon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (jus Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 as Spotted 250 gals 15% acid; broke @ 5500# & immediate csg. AR&P = 3.5 BPM @ 41000 established pump-in rate of 4 BPM @ 2200#. Pum mud flush followed by 1230 ax Halliburton Lite & 5# Salt/sx; pulled stinger from CR and revers	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.)* abandon Bone Springs I ast below Bone Springs I ast below Bone Springs S BPM @ 4500#. Set Hallin 025'; AR&P = 2 BPM @ 4 alliburton cemented w/2 k w/.3 of 1% CFR-2. diately established ci #. Set cement retaine ped 250 gals 15% acid w/.3 of 1% CFR-2, .3 o ed out excess cement.	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#. 100 sx Class rc to surface r @ 8728' & with 500 gals f 1% Halad 22- Pulled 1 jt
ABANDON [•] (other) X Ab _a ndon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (just Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 so Spotted 250 gals 15% acid; broke @ 5500# & immediate csg. AR&P = 3.5 BPM @ 4100 established pump-in rate of 4 BPM @ 2200#. Pum mud flush followed by 1230 sx Halliburton Lite & 5# Salt/sx; pulled stinger from CR and revers tbg; removed BOP & installed X-tree.	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa- int to this work.)* abandon Bone Springs I abandon Bone Springs I abandon Bone Springs I abandon Bone Springs I abandon Bone Springs I below Bone Springs I abandon Bone Springs I below Bone Springs I abandon Bone Springs I below Bone Springs I abandon Bone Springs I aba	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#. 100 sx Class rc to surface r @ 8728' & with 500 gals f 1% Halad 22- Pulled 1 jt
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (just Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 so Spotted 250 gals 15% acid; broke @ 5500# & immediate csg. AR&P = 3.5 BPM @ 4100 established pump-in rate of 4 BPM @ 2200#. Pum mud flush followed by 1230 sx Halliburton Lite & 5# Salt/sx; pulled stinger from CR and revers tbg; removed BOP & installed X-tree.	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa- int to this work.)* abandon Bone Springs I abandon Bone Springs I abandon Bone Springs I abandon Bone Springs I abandon Bone Springs I below Bone Springs I abandon Bone Springs I below Bone Springs I abandon Bone Springs I below Bone Springs I abandon Bone Springs I aba	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#. 100 sx Class rc to surface r @ 8728' & with 500 gals f 1% Halad 22- Pulled 1 jt Pressure-
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (jus Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 so Spotted 250 gals 15% acid; broke @ 5500# & immediate csg. AR&P = 3.5 BPM @ 4100 established pump-in rate of 4 BPM @ 2200#. Pum mud flush followed by 1230 sx Halliburton Liter & 5# Salt/sx; pulled stinger from CR and revers tbg; removed BOP & installed X-tree. WOC 72+ hours. Drilled cement retainer & cement tested perfs @ 8780' & broke @ 2800#. Pumped by Subsurace Safety Valve: Manu. and Type	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.) ^a abandon Bone Springs I ab below Bone Springs S BPM @ 4500#. Set Hallin D25'; AR&P = 2 BPM @ 4 alliburton cemented w/2 k w/.3 of 1% CFR-2. diately established ci #. Set cement retaine ped 250 gals 15% acid to w/.3 of 1% CFR-2, .3 o ed out excess cement. t with reverse unit. BPM @ 1800#. Continued M @a	pertinent dates, ice locations and Lime). Sand) Surton cement 500#. 100 sx Class rc to surface r @ 8728' & with 500 gals f 1% Halad 22- Pulled 1 jt Pressure- ge 4 Ft.
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (jus Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 so Spotted 250 gals 15% acid; broke @ 5500# & immediate csg. AR&P = 3.5 BPM @ 4100 established pump-in rate of 4 BPM @ 2200#. Pum mud flush followed by 1230 sx Halliburton Liter & 5# Salt/sx; pulled stinger from CR and revers tbg; removed BOP & installed X-tree. WOC 72+ hours. Drilled cement retainer & cement tested perfs @ 8780' & broke @ 2800#. Pumped by Subsurace Safety Valve: Manu. and Type	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa int to this work.) ^a abandon Bone Springs I ab below Bone Springs S BPM @ 4500#. Set Hallin D25'; AR&P = 2 BPM @ 4 alliburton cemented w/2 k w/.3 of 1% CFR-2. diately established ci #. Set cement retaine ped 250 gals 15% acid to w/.3 of 1% CFR-2, .3 o ed out excess cement. t with reverse unit. BPM @ 1800#. Continued M @a	pertinent dates, ice locations and Lime). Sand) Surton cement 500#. 100 sx Class rc to surface r @ 8728' & with 500 gals f 1% Halad 22- Pulled 1 jt Pressure- ge 4 Ft.
ABANDON* (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Vann ran wireline-set CIBP & set @ 9300' KB (to Perforated 4 (90°) squeeze holes @ 9025' KB (jus Ran RTTS pkr and established pump-in rate of 2 I retainer @ 9005' KB & cement block-squeezed @ 90 Perforated 4 (90°) squeeze holes @ 8780' KB & Ha H w/.3 of 1% CFR & .3 of 1% Halad 22-A and 50 so Spotted 250 gals 15% acid; broke @ 5500# & immediate csg. AR&P = 3.5 BPM @ 4100 established pump-in rate of 4 BPM @ 2200#. Pum mud flush followed by 1230 sx Halliburton Liter & 5# Salt/sx; pulled stinger from CR and reverss tbg; removed BOP & installed X-tree. WOC 72+ hours. Drilled cement retainer & cement tested perfs @ 8780' & broke @ 2800#. Pumped ½ Subsurace Safety Valve: Manu. and Type 18. Increby pertify that the foregoing is true and correct Area Superve	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa- int to this work.)" abandon Bone Springs I abandon Bone Springs S BPM @ 4500#. Set Hallin 025'; AR&P = 2 BPM @ 4 alliburton cemented w/2 k w/.3 of 1% CFR-2. diately established ci- t. Set cement retainer ped 250 gals 15% acid w w/.3 of 1% CFR-2, .3 o ed out excess cement. t with reverse unit. BPM @ 1800#. Continued M @a	pertinent dates, ice locations and Lime). Sand) Surton cement 500#. 100 sx Class rc to surface r @ 8728' & with 500 gals f 1% Halad 22- Pulled 1 jt Pressure- ge 4 Ft.
ABANDON [•] (other) X Abandon Atoka 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statistication in the statistication of	is Complete Bone Spring te all pertinent details, and give directionally drilled, give subsurfa- int to this work.)" abandon Bone Springs I as below Bone Springs S BPM @ 4500#. Set Hallin 025'; AR&P = 2 BPM @ 42 alliburton cemented w/2 k w/.3 of 1% CFR-2. diately established ci- #. Set cement retaine ped 250 gals 15% acid of w/.3 of 1% CFR-2, .3 o ed out excess cement. t with reverse unit. BPM @ 1800#. Gontinued M @a disor DATE February 22 office use)	pertinent dates, ice locations and Lime). Sand) Sourton cement 500#. 100 sx Class rc to surface r @ 8728' & with 500 gals f 1% Halad 22- Pulled 1 jt Pressure- ge 4 Ft. c, 1982

. ~