

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Amoco Production Company ✓

3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 990' FEL, Sec. 4
AT TOP PROD. INTERVAL: (Unit I, NE/4, SE/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM-13396

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED

8. FARM OR LEASE NAME MAR 26 1981
Federal CC

9. WELL NO. O. C. D.
1

10. FIELD OR WILDCAT NAME ARTESIA, OFFICE
Und. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4-19-24

12. COUNTY OR PARISH Eddy 13. STATE NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3262' GL

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-331)

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 2-23-81, Warton Drilling Co. (Rig #3) spudded a 17-1/2" hole. Drilled to a TD of 402' and ran 13-3/8" 48# H-40 casing set at 402'. Cemented with 300 SX Thixset with additives and 500 SX Class "C" with additives. Plugged down at 6:45 a.m. 2-24-81. Circulated 400 SX. WOC 18 hrs. and test casing with 1000# for 30 min. Tested OK. Reduced hole to 12-1/4" and resumed drilling.

0+5-USGS, A 1-Hou 1-Susp 1-GLF 1-W. Stafford, Hou 1-HNG
1-Read X Stevens 1-Pennzoil 1-Yates, A 1-Abby Corp. 1-Coquina
1-Perry Gas, O 1-Patrick Petro, M

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ronald L. Foster TITLE Admin. Analyst DATE 3-16-81

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

MAR 19 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side