

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator MITCHELL ENERGY INC.		Lease RUNYAN 30 ST. COM		Well # 1	
Location of Well	Unit 990FSL 1980FWL N	Section 30	Township 19	Range 23	County Eddy
Drilling Contractor	?		Type of Equipment ROTARY ECT 2-27-81		

* WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17.5"	13 3/8"	54.5 #		300'	Surface
12.25"	8 5/8"	24 #		1600'	Surface
7 7/8"	4 1/2"	11.6 #		8000'	6000'

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required 1100

Type of Shoe used Guide Float collar used INSERT Btm 3 jts welded YES

TD of hole 1600 Set 1607 Feet of 8 5/8" Inch 24 # Grade K-55

(New)-used csg. @ 1595' with 250 sacks neat cement around shoe C.I.C w 1% CaCl.
+ 200 sax THIC-GBT additives 10 # 1/4 GILSONITE, 1/4 # celbseal, 12% CaCl, + 650 sxs. Lite w/ 5 # gilsmit
+ 1/4 # 1/4 GILSONITE

Plug down @ 3:30 (AM) (PM) Date 6/8/81

Cement circulated YES. No. of Sacks 400 sxs.

Cemented by Western Co. of N. Am. Witnessed by Larry Brooks.

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Drilling completed w/ full returns

Basket @ 752'

Cent. @ 1555', 1470', 1386', 793', 709'