

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

JUL 15 1981

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER-

7. Unit Agreement Name

Name of Operator
Yates Petroleum Corporation

8. Farm or Lease Name
Emma "QE" Com

Address of Operator
207 South 4th St., Artesia, NM 88210

9. Well No.
1

Location of Well
UNIT LETTER K 1980 FEET FROM THE South LINE AND 1650 FEET FROM

10. Field and Pool, or Wildcat
Und. Hoag Tank Morrow

THE West LINE, SECTION 22 TOWNSHIP 19S RANGE 24E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3681' GL

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK PLUG AND ABANDON
TEMPORARILY ABANDON CHANGE PLANS
REPAIR OR ALTER CASING OTHER

REMEDIAL WORK ALTERING CASING
COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
CASING TEST AND CEMENT JOB OTHER

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 9:45 AM 7-5-81. TD 280'. Ran 6 jts. of 13-3/8" 48# H-40 (403') of casing set at 280'. 1-notched guide shoe at 280'. Flapper float insert at 240'. Stuck casing at 270'. Could not break circulation or move pipe. Ran one inch outside to cement up. Cemented w/200 sacks Thixolite, 2# Permacheck, 1/2# celloseal, 250 sacks 65-35 Poz, 1/4# celloseal and 1# Permacheck. Tailed in w/150 sacks Class "C" 2% CaCl. Finished cementing at 4:00 PM 4-7-81. Cement circulated 47 sacks. WOC 14 hrs. Reduced hole to 12-1/2" Drilled plug and resumed drilling. TD 996'. Ran 25 jts. of 8-5/8" 24# J-55 ST&C casing set at 996'. 1-cement guide shoe at 996'. Insert flapper float at 956'. Cemented w/200 sacks 65-35 Pacesetter, 1# Permacheck, 1/2# celloseal, 600 sacks 65-35 Pacesetter, 1/4# celloseal and 3% CaCl. Tailed in w/150 sacks Class "C" Neat 2% CaCl. PD 8:20 PM 7-9-81. Bumped plug to 500 psi, released pressure and float did not hold. SI. Cement circulated 57 sacks to pits. WOC 23 hrs. and 40 min. Nippled up and tested to 1000#, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Engineering Secretary DATE 7-15-81

APPROVED BY [Signature] TITLE SUPERVISOR, DISTRICT II DATE JUL 20 1981

CONDITIONS OF APPROVAL, IF ANY: