

UN. STATES OF NEW MEXICO  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Tenneco Oil Company ✓

3. ADDRESS OF OPERATOR

6800 Park Ten Bl, San Antonio, TX 78213

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL &amp; 2310' FWL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) set casing ☐

5. LEASE

NM-03909377A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

HJ-13 Fed Com

JUL 2 1981

9. WELL NO.

1

O. C. D.

10. FIELD OR WILDCAT NAME ARTESIA, OFFICE

Lusk Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 13, T19S, R31E

12. COUNTY OR PARISH 13. STATE

Eddy

Texas

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3557.9' GR

(NOTE: Report depths of multiple completion or zone change on Form 9-331-C)

JUL 02 1981

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6/24/81 Ran 91 jts 8-5/8", 32#, K55, 8rd STC Csg. set at 4101' Cmt w/420 sxs Cl "C" + 2% Lo-dense 8#/sx A-S salt + 1/2#/sx celoflakes + 5 D-7 Gilsonite + 200 sxs Cl C + 1% CaCl<sub>2</sub>. Did not bump plug. Could not open "DV" tool. Calc. top of Cmt. 2400'. Pumped plug down w/H<sub>2</sub>O + mud, 250 bbl, plug down at 4:30 a.m.

6/25/81 Press up on plug to 3,000 psi, Lost wt on indicator, ran temp. survey, RIH w/1" pipe, tag cmt. at 2330'. Cmt. thru 1". w/250 sxs, POOH w/15 doubles of 1".

6/26/81 TIH w/1" &amp; tag cement. Cmt w/250 sxs, TIH w/1" &amp; tag cmt., circ. &amp; cmt. w/250 sxs, TIH &amp; tag cmt., circ 600 sxs cmt to surf. W.O.C. - 43 1/2'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Anita Gray

TITLE Production Analyst DATE June 30, 1981

APPROVED BY  
CONDITIONS OFACCEPTED FOR RECORD (This space for Federal or State office use)  
ROGER A. CHAPMAN

APPROVAL, IF ANY:

JUL 2 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side