

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

MAR 11 1982

O. C. D.

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
State 648

SUNDY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation /

3. Address of Operator
207 South 4th St., Artesia, NM 88210

4. Location of well
UNIT LETTER K FEET FROM THE South LINE AND 1980 FEET FROM
THE West LINE, SECTION 8 TOWNSHIP 19S RANGE 28E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
North Millman Unit

9. Well No.
3

10. Field and Pool, or Wildcat
South Millman Morrow

15. Elevation (Show whether DF, RT, GR, etc.)
3550' KB

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set CIBP at 10980' w/35' of cement on top. WIH and perforated 10866-10915' w/10 .50" holes as follows: 10866, 68, 69, 71, 74½, 82, 92, 99, 10912½ & 15'. Acidized perms 10866-10915' w/2500 gallons 7½% Morrowflo acid and N2 plus 8 ball sealers. Swabbed well down. Set standing valve in packer at 10822'. Come off on/off tool. POOH. WIH and perforated 10568-600' w/13 .50" holes as follows: 10568-77' (10 holes) and 10598-600' (3 holes). Acidized well as follows: 10598-600' w/3000 gallons 7½% Morrowflo acid; 10568-577' w/2200 gallons 7½% Morrowflo acid. Swabbed back load. Small show of gas.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Gressett TITLE Engineering Secretary DATE 3-8-82

APPROVED BY W. A. Gressett TITLE SUPV. OF OPERATIONS, DISTRICT II DATE MAR 15 1982

CONDITIONS OF APPROVAL, IF ANY: