

ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Ralph Nix</u>		Lease <u>Debbie</u>		Well # 	
Location of Well	Unit <u>1980S 660E I</u>	Section <u>11</u>	Township <u>20</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor	<u>Hondo Dring Co</u>		Type of Equipment <u>Rotary ASAP</u>		
* Witness					
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48#</u>		<u>400'</u>	<u>Circ</u>
<u>11</u>	<u>8 5/8</u>	<u>24#</u>		<u>1400'</u>	<u>Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.5#-17#</u>		<u>9600'</u>	<u>350 sy</u>
Casing Data:					
Surface joints of <u>8 5/8"</u> inch <u>24</u> # Grade <u>J-SS</u>					
(Approved) (Rejected)					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>11"</u> Size of Casing <u>8 5/8"</u> Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1237'</u> Set <u>1236'</u> Feet of <u>8 5/8"</u> Inch <u>24</u> # Grade <u>J-SS</u>					
New-used csg. @ <u>1236'</u> with <u>200 2%oc</u> sacks neat cement around shoe					
+ <u>400</u> sax <u>Hall, Lite</u> additives <u>5# gel., 1/4# Floreal, 2%oc</u>					
Plug down @ <u>5845</u> (AM) (<u>PM</u>) Date <u>9/16/81</u>					
Cement circulated <u>Yes</u> No. of Sacks <u>224 sx</u>					
Cemented by <u>Halliburton</u> Witnessed by <u>Mrs. Stillfield</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					
Centulips 2 1197'-1117' host ddy head 2 884'					