

YATES PETROLEUM CORPORATION
Sara AHA Com #1
Section 11-T20S-R24E
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

5-1/2" casing at 1250'. POOH and rigged down wireline. RIH with packer and set packer at 867'. Pressured up to 1500 psi. POOH with packer. RIH open ended to 1312'. Spotted 25 sacks Class C Neat cement from 1312-1071'. POOH. WOC. Shut well in for night.
10-10-2002 - RIH with tubing and tagged cement at 1063'. POOH. Rigged up wireline. RIH and perforated 5-1/2" casing at 465'. POOH and rigged down wireline. RIH with packer and set packer at 94'. Pressured up to 1500 psi. POOH with packer. RIH open ended to 515'. Spotted 25 sacks Class C Neat cement from 515-274'. POOH. WOC 4 hours. RIH and tagged cement at 287'. POOH. Nippled down BOP and tubing equipment. RIH to 60'. Circulated 10 sacks Class C Neat cement to surface. POOH. Rigged down pulling unit and plugging equipment. Installed regulation abandonment marker. PLUGGED AND ABANDONED - FINAL REPORT. Plugging completed 10-9-2002.

Kenna Clark

10-10-2002
10-10-2002