

JAN 4 1982

U. S. GEOLOGICAL SURVEY
 UNITED STATES DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY
 N. M. OIL CONS. COMMISSION
 P. O. BOX 1230
 HOBBS, NEW MEXICO 5. EL
 6. 15

Form Approved.
Budget Bureau No. 42-R1424
ARTESIA, OFFICE

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

- NM-045276
 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
 7. UNIT AGREEMENT NAME
 8. FARM OR LEASE NAME
 Preston Federal
 9. WELL NO.
 2
 10. FIELD OR WILDCAT NAME
 Cisco/Morrow
 11. SEC., T., R., M., OR BLK. AND SURVEY OR
 AREA
 Sec. 34, T-20S, R-24E
 12. COUNTY OR PARISH
 Lea
 13. STATE
 NM
 14. API NO.
 15. ELEVATIONS (SHOW DF, KDB, AND WD)

SUBSEQUENT REPORT OF:

- | |
|--|
| |
| |
| |
| |
| |
| |
| |

(other) TD, ran production csg

RECEIVED
(NOTE: Report changed)
DEC 16 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Reached TD of 9750' on 11/24/81. Ran 7", 26[#], L-80 & K-55, LTC & buttress
csg set at 9596', FC at 9514', DV at 7026'. 1st stage cement: 800sx 50/50
Poz, tail w/ 100sx Class Hcmt. 2nd stage cement: 2080sx 50/50 Poz, tail w/
150sx Class Hcmt. Circulated 25sx cement to surface.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. ROGER A. CHAPMAN

SIGNED Wm. A. B. [Signature] TITLE Administrative Supervisor

DATE December 14, 1981

(This space for Federal or State office use)

APPROVED BY _____
 CONDITIONS OF APPROVAL, IF ANY:
 ROSWELL, NEW MEXICO

TITLE _____ DATE _____