## Submit 3 Copies

## State of New Mexico

| d              | ${\mathfrak c}_\perp$ |
|----------------|-----------------------|
| Form C-103     | OP                    |
| Revised 1-1-89 | VY                    |

to Appropriate District Office . Energy, Minerals and Natural Resources Department DISTRICT OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-015-23931 Santa Fe. New Mexico 87504-2088 **DISTRICT II** P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease STATE FEE 📙 DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 1100 F & 1991 6. State Oil & Gas Lease No. B-8096 SUNDRY NOTICES AND REPORTS ON WELLSTESIA OFFICE ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: OIL X WELL | Conoco "7" State OTHER 2. Name of Operator 8. Well No. Mitchell Energy Corporation 3. Address of Operator 9. Pool name or Wildcat P. O. Box 4000, The Woodlands, TX 77387 E. Millman (Queen-Greyburg) 4. Well Location 660 Feet From The North 1880 East Unit Letter B Line and \_ Feet From The Township 19S 29E Eddy 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3377' Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: X PERFORM REMEDIAL WORK PLUG AND ABANDON **ALTERING CASING** REMEDIAL WORK TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMEN **PULL OR ALTER CASING CASING TEST AND CEMENT JOB** OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Plug and Abandon as per the following procedure: ¥ 25°5X3 POOH w/rods, pump, and 2 3/8" tbg. RIH w/tbg and set 35' cmt plug in 4 1/2" csg above top perf (2199'). Tag plug. Spot 25 sx plug @ top of Queen (1763'). Spot 25 sx plug at base of salt (666'). Spot 25 sx plug @ 8 5/8" shoe (379') and tag. Spot 10 sx cmt plug @ surface. Weld on cap and erect permanent abandonment marker. Load hole with gelled brine between all plugs. mmr Engineer SIGNATURE James Blount type or print name As noted above DATE 11-21-91 S SHEETES

CONDITIONS OF APPROVAL, IF ANY