

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Chama Petroleum Company

3. ADDRESS OF OPERATOR
5447 Glen Lakes Dr., Dallas, Texas 75231

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980 FSL + 1980 FEL
AT SURFACE: 3435 GL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: 9800'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Surface & Intermediate Casing

RECEIVED
DEC 22 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-14-81: Spud 17 1/2" surface hole at 1:30 A.M. 12-13-81, finished 17 1/2" surface hole at 3:00 P.M., ran 9 joints 13 3/8" 48# ST&C casing with guide shoe on bottom, total of 379' of pipe, set at 366' KB with 305' pipe in ground, pumped 375 sacks Class "C" cement containing 2% calcium chloride, displaced with fresh water leaving estimated 30' cement in bottom joint, circulated 175 sacks cement to pit, cement displaced at 8:40 P.M., waited on cement 4 hours.

12-15-81: Drilling @ 535' in Redbed, M.W. 8.5, Vis 28, PH 9, Pump Pressure 1150, Weight on Bit 50,000, RPM 50

12-16-81: Drilling @ 1046' in sand & lime, M.W. 8.4, Vis. 28, PH 9.5, Chlorides 600, Calcium 140, Pump Pressure 1250, Strokes 56, Weight on Bit 50,000, RPM 50, Totco at 562' was 3/4".

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE _____ DATE _____

APPROVED BY
CONDITIONS OF

ACCEPTED FOR RECORD
PETER W. CHESTER

DEC 23 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side