

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Chama Petroleum Company

3. ADDRESS OF OPERATOR

5447 Glen Lakes Dr., Dallas, Texas 75231

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 3435 GL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: 9800'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Surface & Intermediate Casing

SUBSEQUENT REPORT OF:

□ □ □ □ □ □ □ □

RECEIVED
(NOTE: Reproduction)
DEC 22 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWell, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-17-81: Drilling @ 1350' in sand & lime, M.W. 8.3, Vis. 27, PH 10, Chlorides 600, Calcium 140, Pump Pressure 1250, Strokes 56, Weight on Bit 50,000, RPM 60, Totco at 1075' was 1/40, Totco at 1350' was 1/40.

12-18-81: Drilling @ 1450' in sand & lime, M.W. 8.4, Vis. 28, PH 10.5, Chlorides 600, Calcium 140, Pump Pressure 1250, Strokes 54, Weight on Bit 45,000, RPM 50, ran 31 joints 8 5/8" OD 24# K-55 ST&C casing (1356' of pipe) set at 1350' KB, ran type M scalloped shoe on bottom, insert float 1 joint up, 1 centralizer each on bottom 4 joints, pumped 300 sacks Halliburton light containing 1/4# flocele & 5# gilsonite containing 2% calcium chloride followed with 200 sacks class "C" cement containing 2% calcium chloride, displaced cement with 85 bbls. fresh water, bumped plug at 11:30 A.M. 12-17-81, float held, circulated est. 200 cement to pit. 10 hr. waiting on cement, pressured up on casing to 1500 psig & held O.K.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE President DATE 12/18/81

SIGNED W. A. [illegible] TITLE _____
 ACCEPTED FOR RECORD (This space for Federal or State office use)
 PETER W. CHESTER
 APPROVED BY _____ TITLE _____
 CONDITIONS OF APPROVAL DEC 23 1981

APPROVED BY _____
CONDITIONS OF _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side