

NEW MEXICO OIL CONSERVATION BOARD
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Robert N. Enfield</u>		Lease <u>Lee</u>		Well # <u>1</u>	
Location of Well	D Unit <u>660 FWL</u> <u>660 FNL</u>	Section <u>13</u>	Township <u>19</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>Collier Drilling Co.</u>		Type of Equipment <u>Rotary</u> <u>11-25-81</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>12 1/4 - 11"</u>	<u>8 5/8"</u>	<u>24 #</u>		<u>1150'</u>	<u>500 sk</u>
<u>7 7/8"</u>	<u>4 1/2"</u>	<u>10.60 #</u>		<u>2600'</u>	<u>570 sk</u>
Casing Data:					
Surface _____ joints of <u>7"</u> inch <u>20</u> # Grade <u>J-55</u>					
(<u>Approved</u>) (Rejected)					
Inspected by <u>M.S.</u> date <u>12/17/81</u>					
Cementing Program					
Size of hole <u>9 7/8"</u> Size of Casing <u>7"</u> Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm <u>2</u> jts welded <u>yes</u>					
TD of hole <u>1307'</u> Set <u>1302'</u> Feet of <u>7"</u> Inch <u>20</u> # Grade <u>J-55</u>					
(<u>New</u>) used csg. @ <u>1302'</u> with <u>500</u> sacks neat cement around shoe					
+ _____ sack _____ additives					
Plug down @ <u>6:30</u> (AM) (<u>PM</u>) Date <u>12/18/81</u>					
Cement circulated <u>yes</u> No. of Sacks <u>50</u>					
Cemented by <u>Hullington</u> Witnessed by <u>Mike Stillfield</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

centulizers @ 1262' - 1222' - 1182' - 1102' Full returns to TD.					