

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

6. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
648

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (STATE C-101) FOR SUCH PROPOSALS.)

RECEIVED

FEB 2 1982

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Yates Petroleum Corporation /

O. C. D.
ARTESIA, OFFICE

7. Unit Agreement Name

3. Address of Operator
207 South 4th St., Artesia, NM 88210

8. Farm or Lease Name
Millman SB State

4. Location of Well
UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
East THE LINE, SECTION 16 TOWNSHIP 19S RANGE 28E NEIGH.

9. Well No.
1

10. Field and Pool, or Willcut
S. Millman Morrow

15. Elevation (Show whether DF, RT, GR, etc.)
3479' GR

11. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPER. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
Production Casing, Perforate ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11300'. Ran 263 joints of 5-1/2" N-80 17# casing set at 11300'. 1-regular guide shoe set at 11300'. Float collar set at 11260'. Cemented w/500 sacks 65/35 Poz, 6% fluid loss control, 5% friction reducer, 4% KCL. Tailed in w/175 sacks Class "C", 6% fluid loss, .5% friction reducer, 4% KCL. PD 5:35 PM 1-23-82. Bumped plug to 1000 psi, released pressure and float held okay. WOC. Perforated 11073-11083' w/40 .50" holes with tubing conveyed gun. Well cleaned up and stabilized at 880 psi on 3/4" choke = 12800 mcfpd.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature]

TITLE Engineering Secretary

DATE 2-1-82

APPROVED BY [Signature]

TITLE SUPERVISOR, DISTRICT II

DATE FEB 2 1982

CONDITIONS OF APPROVAL, IF ANY: