

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM-14747

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Panos Federal #1

9. API Well No.

30-015-24026

10. Field and Pool, or Exploratory Area

Undesignated Cisco

11. County or Parish, State

Eddy Co., NM

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FEL of Section 1-T19S-R23E (Unit H, SENE)

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

CONTINUED FROM PREVIOUS PAGE:

at 4609'. POOH with tubing to 3550'. Mixed and pumped 30 sacks Class C cement from 3550-3450' (in 7-7/8" hole). POOH with tubing to 1759'. Mixed and pumped 40 sacks Class C 2% CaCl<sub>2</sub> from 1759-1659' (in 8-5/8" casing). POOH with tubing to 1000'. WOC 4 hours. TIH with tubing and tagged top of cement at 1730'. Mixed and pumped 40 sacks Class C 2% CaCl<sub>2</sub> cement from 1730-1659' (in 8-5/8" casing). POOH with tubing. WOC 4 hours. TIH with tubing and tagged top of cement at 1660'. POOH with tubing to 1000'. Shut well in for night. NOTE: Don Early w/BLM-Carlsbad witnessed cement plugs.  
9-12-96 - TIH with tubing and tagged top of cement at 1650'. POOH with tubing to 372'. Mixed and pumped 30 sacks Class C cement from 372-272' (in 8-5/8" casing). POOH with tubing to 100'. Mixed and pumped 25 sacks Class C cement from 100' to surface. POOH with tubing. Nippled down BOP. Rigged down pulling unit. Cleaned location. Installed regulation abandonment marker. PLUGGED AND ABANDONED - FINAL REPORT. Plugging completed 9-12-96.

14. I hereby certify that the foregoing is true and correct

Signed

*Rustyn Klein*

Title Production Clerk

Date Sept. 12, 1996

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: