

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 19441

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gulf Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 31 - T19S-R30E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

MORRIS R. ANTWEIL

3. ADDRESS OF OPERATOR

P. O. Box 2010, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FNL & 1980' FWL of Section 31

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3323.1 GR

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1660' TD; 1618' PBTD; Perforations 1626'-1649' (13 holes);  
Squeezed with 125 sx. Perforations 1588'-1600' Produced 10.2 BWPD w/ trace of oil.  
4 1/2" casing circulated to surface with cement.  
Proposed to Plug and Abandon as follows:

1. Spot 15 sk plug from 1450' to 1618' across perms. Tag plug.
- \* 2. Spot 15 sk plug from 275' to 425' across 7-5/8" casing shoe inside 4 1/2" casing.
3. Spot 15 sk surface plug with marker.

\* 2. Change in plugging procedure because well in Secretary's Potash area.  
Cement plug at base of salt 1550'-1250'  
Cement plug at top of salt 425'-125'. P.W.C.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 7/13/82

(This space for Federal or State office use)

(Orig. Sgd.) PETER W. CHESTER

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FOR

JAMES A. GILLHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side