

dsr

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR
Bel-Dyn, Inc. Properties

3. ADDRESS OF OPERATOR
P.O. Box 136 Lovington, N.M. 88260

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Completion		

5. LEASE

NM-0560353

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Hale Federal

9. WELL NO.

OCT 8 1982

10. FIELD OR WILDCAT NAME

Shugart - Y. SP. ARTESIA OFFICE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

1-19S-30E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3506 DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled (WEK-Rotary) to 3500', Welex logged O.H.: Sidewall, Nuutron and Guard-Forxo. Ran and cemented (circulated) 5 1/2"-15.5# casing to 3480'. Perforated and acidized Queen sand perfs and fracked perfs. With 48,000# sand and 32,000 gals. gelled brine water. Swabbed back load-oil and gas.
Spudded: 7-13-82 T.D.: 7-21-82
8 5/8" 20# set at 618', 5 1/2" 15.5# set at 3480'
Hole size 12 1/4" Hole size 7 7/8"

Subsurface Safety Valve: Manu. and Type


Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Manager/Operator DATE September 23, 1982

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE DATE



RECEIVED

SEP 28 1982

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO