

				TRUE		RECTANGULAR		DOGLEG
MEASURED	DRIFT	DRIFT	COURSE	VERTICAL	C O O R D I N A T E S	SEVERITY		
DEPTH	ANGLE	DIRECTION	LENGTH	DEPTH	FEET	DG/100FT		
FEET	D M	D	FEET	FEET				
3007.	0 0	0	0.	3007.00	0.00	0.00	0.00	
3069.	1 0	N 31 E	62.	3069.00	0.46 N	0.28 E	1.61	
3101.	1 0	N 32 E	32.	3100.99	0.94 N	0.57 E	0.05	
3195.	1 15	N 42 E	94.	3194.97	2.41 N	1.68 E	0.34	
3295.	0 45	N 24 E	100.	3294.96	3.87 N	2.63 E	0.58	
3383.	0 45	S 64 E	88.	3382.95	4.22 N	3.60 E	1.23	
3477.	0 30	S 76 E	94.	3476.95	3.87 N	4.56 E	0.30	
3572.	1 0	N 54 E	95.	3571.94	4.10 N	5.74 E	0.82	
3666.	1 0	N 56 E	94.	3665.92	5.04 N	7.08 E	0.04	
3760.	1 15	N 50 E	94.	3759.90	6.13 N	8.56 E	0.29	
3854.	1 0	S 1 E	94.	3853.89	7.11 N	9.98 E	0.27	
3948.	1 0	N 60 E	94.	3947.88	8.11 N	11.33 E	0.17	
4042.	1 15	N 78 E	94.	4041.83	8.98 N	13.03 E	0.41	
4136.	1 0	N 59 E	94.	4135.84	9.68 N	14.73 E	0.42	
4230.	1 0	N 49 E	94.	4229.82	10.64 N	16.05 E	0.19	
4324.	0 45	N 67 E	94.	4323.81	11.40 N	17.26 E	0.39	
4418.	0 45	N 80 E	94.	4417.80	11.75 N	18.44 E	0.18	
4512.	0 45	N 73 E	94.	4511.79	12.04 N	19.64 E	0.10	
4606.	0 45	N 68 E	94.	4605.79	12.45 N	20.80 E	0.07	
4700.	0 30	N 81 E	94.	4699.78	12.72 N	21.78 E	0.30	
4794.	0 30	N 46 E	94.	4793.78	13.08 N	22.50 E	0.32	
4888.	0 45	N 1 W	94.	4887.77	14.00 N	22.89 E	0.58	
4982.	1 0	N 16 W	94.	4981.76	15.42 N	22.67 E	0.36	
5076.	1 0	N 2 E	94.	5075.75	17.04 N	22.48 E	0.33	
5170.	1 30	N 0 W	94.	5169.72	19.09 N	22.51 E	0.53	
5264.	1 15	N 3 W	94.	5263.70	21.34 N	22.45 E	0.28	
5358.	1 30	N 19 E	94.	5357.67	23.56 N	22.76 E	0.62	
5452.	1 30	N 34 E	94.	5451.64	25.76 N	23.86 E	0.42	
5546.	1 30	N 12 E	94.	5545.60	28.01 N	24.81 E	0.61	
5640.	1 0	N 14 E	94.	5639.58	30.01 N	25.28 E	0.53	

Eastman
Whipstock