

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
	Lwr				
T. Anhy	T. Canyon	7027	T. Ojo Alamo	T. Penn. "B"	
T. Salt	T. Strawn	7608	T. Kirtland-Fruitland	T. Penn. "C"	
B. Salt	T. Atoka	7830	T. Pictured Cliffs	T. Penn. "D"	
T. Yates	T. Miss		T. Cliff House	T. Leadville	
T. 7 Rivers	T. Devonian		T. Menefee	T. Madison	
T. Queen	T. Silurian		T. Point Lookout	T. Elbert	
T. Grayburg	T. Montoya		T. Mancos	T. McCracken	
T. San Andres	T. Simpson		T. Gallup	T. Ignacio Qtzite	
T. Glorieta	T. McKee		Base Greenhorn	T. Granite	
T. Paddock	T. Ellenburger		T. Dakota		
T. Blinberry	T. Gr. Wash		T. Morrison		
T. Tubb	T. Granite		T. Todilto		
T. Drinkard	T. Delaware Sand		T. Entrada		
T. Abo	T. Bone Springs		T. Wingate		
T. Wolfcamp Ls	T. Morrow Cl.	8240	T. Chinle		
T. Penn.	T. Chester	8366	T. Permian		
T. Cisco (Bough C)	T. Miss.	8505	T. Penn. "A"		

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet
No. 2, from.....to.....	feet
No. 3, from.....to.....	feet
No. 4, from.....to.....	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	80	80	Surface				
80	1940	1860	Anhydrite, Dolomite				
1940	2110	170	Dolomite				
2110	2430	320	Anhydrite, Chert, Dolomite				
2430	3610	1180	Anhydrite, Sand, Dolomite, Shale				
3610	4400	790	Shale, Anhydrite				
4400	4720	320	Shale, Anhydrite, Sand				
4720	5050	330	Shale, Limestone, Dolomite				
5050	7760	2710	Shale, Lime, Sand				
7760	8190	430	Chert, Sand, Shale, Lime				
8190	8632	442	Sand, Shale				