

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Vates Petroleum Corp		Lease Emma "QE" Com		Well # 2	
Location of Well	Unit 6605 / 1920E 0	Section 21	Township 19	Range 24	County Eddy
Drilling Contractor Empire #15			Type of Equipment Rotary		

*Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48# J-55		275'	300 SX Circ
* 12 1/4	8 5/8	24# J-55		1100'	800 SX Circ
7 7/8	5 1/2 or 4 1/2	155-17# 10.5-11.6#		9000'	600 SX

Casing Data:

Surface 28 joints of 8 5/8" inch 24 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date _____

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 1099' Set 1099' Feet of 8 5/8" Inch 24 # Grade J-55

New-used csg. @ 1099' with 150 2 7/8" sacks neat cement around shoe

+ 650 sax Hall's Lite additives (1/4" celoflakes)

Plug down @ 7:30 (AM) (PM) Date 3/3/82

Cement circulated Yes No. of Sacks 45 SX

Cemented by Halliburton Witnessed by Mike Stullfield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

No centralizers or baskets

Full returns to TD