

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO

RECEIVED

APR 19 1982

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LG-2722

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER-
Name of Operator		
Collier Energy, Inc. ✓		
Address of Operator		
P. O. Box 798, Artesia, New Mexico 88210		
Location of Well		
UNIT LETTER	P	1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE West	LINE, SECTION 23	TOWNSHIP 19S RANGE 27E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
South
9. Well No.
#1
10. Field and Pool, or Wildcat
Wildcat-Grayburg
12. County
Eddy

15. Elevation (Show whether DF, RT, GR, etc.)

1600' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
WELL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>

REMEDIAL WORK	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOBS	<input checked="" type="checkbox"/>
OTHER	<input type="checkbox"/>

ALTERING CASING	<input type="checkbox"/>
PLUG AND ABANDONMENT	<input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

March 29, 1982: Spudded with 10 3/4" bit.

April 5, 1982: Drilled to 280' and ran 280' of 8 5/8" 20# casing. Cemented with 100 Sxs of Class "C" neat, 2% CaCl₂. Didn't circulate. Ran Temperature Survey (Bennet & Cathey). Top of cement at 90' from surface.

April 16, 1982: Ready mixed 8 5/8" surface casing from 90' to surface with 2 yards 1/4" mesh cement (Rose Gravel).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mike Walker TITLE Agent DATE April 17, 1982

OIL AND GAS INSPECTOR

APR 21 1982