

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Exxon Corporation		Lease New Mexico DE "Stable"		Well # 1	
Location of Well	Unit 660N 1980W C	Section 19	Township 19	Range 24	County Eddy
Drilling Contractor —			Type of Equipment Rotary 5-15-82		

*Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot #	New or Used	Depth	Sacks Cement
26	20			40	60 SX Circ
17 1/2	13 3/8	54.5#		300	475 SX Circ
12 1/4	8 5/8	32.0#		1750	1350 SX Circ
7 7/8	5 1/2"	14#-15#-17#		8700 875	915 SX

Casing Data:

Surface joints of **8 5/8"** inch **32** # Grade **K-55**

Approved (Rejected)

Inspected by **M.S.** date **9/29/82**

Cementing Program

Size of hole **11"** Size of Casing **8 5/8"** Sacks cement required

Type of Shoe used **guide** Float collar used **insert** Btm 3 jts welded **yes**

TD of hole **1750'** Set **1750'** Feet of **8 5/8"** inch **32** # Grade **K-55**

New used csg. @ **1750'** with **200 22cc** sacks neat cement around shoe

+ **400** sax **Dowell Lite** additives **5# gilsonite, 1/4# calumet**

Plug down @ **3:45** AM (PM) Date **9/30/82**

Cement circulated **Yes** No. of Sacks **250 sx**

Cemented by **Dowell** Witnessed by **Mike Stubblefield**

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

Centers 2 1750'-1710'-1670'-1630'

Full returns To TD.