

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

JUN 1 1982

2. NAME OF OPERATOR  
Robert N. Enfield

O. C. D.  
ARTESIA, OFFICE

3. ADDRESS OF OPERATOR  
P.O. Box 2431, Santa Fe, NM 87501

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL & 660' FEL of Sec. 18  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
MAY 24 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

Subsequent report of Intermediate casing

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

April 25, 1982: The above captioned well was drilled to a depth of 2200'

April 25, 1982: Ran 53 joints 8-5/8" 24#/ft K-55 ST&C casing. Total pipe ran 2230.38', set at 2200' rotary measurement. Cemented w/850 sacks Halliburton Lite %3 Gilsonite/sk, 44# flocele/sk. 200 sacks Class "C" 2% CaCl2. Plug down at 8:30 PM 4/25/82. Circulated out 100 sks cement, release pressure, float held.

April 28, 1982: Drilling @ 2680', formation lime

Subsurface Safety Valve: Manu. and Type

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert N. Enfield TITLE Operator

Robert N. Enfield

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

