

Nearburg Prod.
Genecca Com 14D #1
14-20-25

Daniel Moore
6/11/92

402-302

13 3/8 @ 352' Circ.

50-850

San Andres 900

1425-1325 Tag

8 5/8 @ 1375' Circ.

561-2461

Glorieta 2511

6855-6755

WC 6805

7660-7560

Penn 7610

(No production in area) Strawn 8283

8850-8750 Tag

TOC @ 8800 by TS

(No production in area) Atoka 9055

Morrow 9340

500-9400 Tag

9584-9689

13,000

NEARBURG PRODUCING COMPANY

WORKOVER RECOMMENDATION

LEASE: Genecco 14-D WELL NO: 1 DATE: 6/10/92
 FIELD: Cemetery (Morrow) ELEVATION: 3429.9
 LOCATION: SEC. 14 T20S R25E

TOTAL DEPTH: 9886 ' PBTD: 9800 '
 CASING RECORD: 8 5/8 @ 1375' 4 1/2 to 9886'
 TUBING RECORD: 86 Jts, open ended to 2871'
 PRODUCING PERFORATIONS: 9584 to 88', 9682 to 89'
 CURRENT PRODUCTION: ~~None~~ NONE
 FORMATION: MORROW
 DOWNHOLE EQUIPMENT DESCRIPTION & DEPTH: N/A.
 REASON FOR WORKOVER: T.A. - Partial CSG @ 2840'
Top cmt 8800'

#3

WORKOVER PROCEDURE

1. P.U. well Sen Rig P.OOH w/ 86 Jts 2 3/8 tubing
2. P.U. CSG, P.OOH & Lay ^{4 1/2} Down w/ CSG. (A)
3. P.U. Tubing SPH ~~SPH~~ spot 25 sx plug from 9500' to 9400' (Tag) 25 sx Plug 8850 - 8750 Tag
4. spot 25 sx plug from 7600' - 7560' Pen
5. spot 25 sx plug from 6855' - 6755' Wolfcamp.
6. spot 25 sx plug from 4500' - 4400' ABO
7. spot 25 sx plug from 2561' - 2461' Globeetha
8. spot 25 sx plug from 1425' - 1325' (STUBB TAG)
9. spot 25 sx plug from 950' - 850' SAN-ANDRES
10. spot 25 sx plug from 402' - 302' SALT
11. spot 10 sx SURFACE plug

(A) spot 25 sx plug 50' in + 50' out of 4 1/2" STUB.
 PLUGS approved by ~~James~~ Darrell with Artesia OGD.

PREPARED BY: I.W. REVIEWED BY: PM DATE: 6/12/92
 DATE: 6/12/92 APPROVED BY: _____ DATE: _____