

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Anadarko Prod Co</u>		Lease <u>Anderson</u>		Well # <u>1</u>	
Location of Well	Unit <u>1980's 1980E I</u>	Section <u>1</u>	Township <u>19</u>	Range <u>2S</u>	County <u>Eddy</u>
Drilling Contractor	<u>Pending</u>		Type of Equipment <u>Rotary</u> <u>5-26-82</u>		

\* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48#		400'	450 Sx Circ
12 1/4	8 5/8	24#		1200'	800 Sx Circ
7 7/8	4 1/2	11.6#		9400'	1200 Sx

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 200

Type of Shoe used Guide Float collar used Float Collar Btm 3 jts welded yes

TD of hole 1335 Set 1328 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 1328 with 200 sacks neat cement around shoe

+ 770 sax Hawco lite additives

Plug down @ 4:30 (AM) (PM) Date 5-31-82

Cement circulated yes No. of Sacks 200

Cemented by Hawco Witnessed by BW Weaver

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: Ran Cement Basket @ 665