

c/91

N. M. CONS. COMMISSION

Drawer DD

Artesia, NM 88210

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ LOST HOLE
2. NAME OF OPERATOR (Phone 396-4334)
JACK PLEMONS (Phone 677-3121)
3. ADDRESS OF OPERATOR
1010 West Avenue "H", Lovington, NM 88260
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FNL & 330' FEL of Sec.
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

- ☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
LC 029353(a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--
7. UNIT AGREEMENT NAME
--
8. FARM OR LEASE NAME
McFADDEN FEDERAL
9. WELL NO.
5
10. FIELD OR WILDCAT NAME
Shugart-Yates-SR-Qn-Entry
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 3-19S-31E
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
--
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3613' G.L.

RECEIVED BY
JUN 27 1984
O. C. D.
ARTESIA, OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
DEC 13 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well on 7-10-82. Well drilled to depth of 702' with rotary tools. On 7-11-82, 702' of 8 5/8" (24#) casing was cemented with 400 sacks (200 Lite & 200 "C" w/2%cc) of cement. Circulated 125 sacks to pit. Witnessed by Pete Hines (USGS).

Drilled out with cable tools but had crooked hole problems. With well at a TD of 740', it was decided to abandon hole and skid 30' west.

Pursuant to telephone conversation, well was plugged as follows:

- 740 - 670' 25-sack cement plug (across shoe)
670 - 20' Mud
20 - 0' 7-sack cement plug.

Dry hole marker will not be installed as well pad and pits will be used for drilling Well #5Y.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James A. Knauf TITLE Agent DATE December 1, 1982
ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JUN 22 1984

NEW MEXICO
*See Instructions on Reverse Side