

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well or to plug a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

OCT 7 1982

2. NAME OF OPERATOR

Yates Petroleum Corporation O.C.D.

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2535 FNL & 584 FWL, Sec. 35-19S-24E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

☒

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM 25865

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Eng TX Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Und. Morrow Near Tank Monitor

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit E, Sec. 35-T19S-R24E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3686' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
AUG 11 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 40' of 20" conductor pipe. Spudded 17-1/2" hole 11:00 AM 7-29-82. Ran 7 joints of 13-3/8" 54# ST&C casing set at 275'. 1-Texas Pattern notched guide shoe at 275'. Insert float at 235'. Cemented w/350 sacks Class "C" 3% CaCl₂. Compressive strength of cement - 1275 psi in 12 hours. PD 2:30 AM 7-30-82. Bumped plug to 900 psi, released pressure and float did not hold. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey and found top of cement at 120'. Ran 1". Tagged cement at 210'. Spotted 50 sacks Class "C" 4% CaCl₂. PD 11:00 AM 7-30-82. WOC 1 hr. Ran 1". Tagged cement at 210'. Spotted 25 sacks Class "C" 4% CaCl₂. PD 12:15 PM 7-30-82. WOC 1 hr and 15 minutes. Ran 1". Tagged cement at 210'. Spotted 25 sacks Class "C" 4% CaCl₂. PD 1:45 PM 7-30-82. WOC 2 hrs and 15 minutes. Ran 1". Tagged cement at 190'. Spotted 25 sacks Class "C" 4% CaCl₂. PD 4:25 PM 7-30-82. WOC 1 hr and 15 minutes. Ran 1". Tagged cement at 160'. Spotted 75 sacks Thixolite. PD 6:00 PM 7-30-82. WOC 1 hr and 30 minutes. Ran 1". Tagged cement at 160'. Spotted 25 sacks Thixolite PD 7:45 PM 7-30-82. WOC 1 hr and 30 minutes.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

(continued)

18. I hereby certify that the foregoing is true and correct

SIGNED

Engineering Secty DATE 8-3-82

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

OCT 5 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side