

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR  
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2535 FNL & 584 FWL, Sec. 35-19S-24E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Intermediate Casing		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Ran 27 joints of 8-5/8" 24# casing set at 1083'. 1-regular guide shoe set 1083'. Insert float set 1043'. Cemented w/630 sx Pacesetter Lite, 10#/sx Gilsonite, 1/4#/sx celloseal & 2% CaCl<sub>2</sub>. Tailed in w/150 sx Class C 2% CaCl<sub>2</sub>. Compressive strength of cement - 1250 psi in 12 hrs. PD 5:15 PM 8-2-82. Bumped plug to 500 psi, released pressure & float held okay. Cement did not circulate. WOC 8 hrs. Ran Temperature Survey & found top of cement at 630'. Ran 1". Tagged cement at 635'. Spot'd 50 sx Class C 3% CaCl<sub>2</sub>. PD 2:30 AM 8-3-82. WOC 2 hrs. Ran 1". Tagged cement at 630'. Spot'd 50 sx Class C 3% CaCl<sub>2</sub>. PD 4:40 AM 8-3-82. Ran 1". Tagged cement at 550'. Spot'd 25 sx Class C Neat. PD 7:45 AM 8-3-82. WOC 1 hr & 45 min. Ran 1". Tagged cement at 490'. Spot'd 25 sx Class C 3% CaCl<sub>2</sub>. PD 9:45 AM 8-3-82. WOC 1 hr & 15 min. Tagged cement at 336'. Ran 1". Spot'd 50 sx Class C 3% CaCl<sub>2</sub>. PD 11:15 PM 8-3-82. WOC 2 hrs. Ran 1". Tagged cement at 301'. Spot'd 50 sx Class C 3% CaCl<sub>2</sub>. PD 1:30 PM 8-3-82. WOC 4 hrs. Ran 1". Tagged cement at 252'. Spot'd 60 sx Thixolite & 1/4#/sx celloflake. PD 5:45 PM 8-3-82. WOC 1 hr & 30 min. Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

(continued)

SIGNED David R. Glass TITLE Engineering Secty DATE 8-9-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY  
CONDITIONS OF

APPROVAL IF ANY

OCT 14 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

5. LEASE

NM 25865

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Eng TX Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Und. Morrow

11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA

Unit E, Sec. 35-T19S-R24E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3686' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
AUG 11 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO