Form 9-331 Dec. 1973	Form Approved. Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-14758
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME Huber Federal
1. oil gas ⊠ other OCT 2 6 1982	9. WELL NO. #2
2. NAME OF OPERATOR Chama Petroleum Company ARTESIA, OFFICE	10. FIELD OR WILDCAT NAME Undesignated Morrow
3. ADDRESS OF OPERATOR 5447 Glen Lakes Dr., Dallas, Texas 75231	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA <u>Sec. 3. T-20-S, R-25-E</u>
below.) at surface: 1650' FNL & 1980' FEL of Sec. 3 at top prod. interval:	12. COUNTY OR PARISH Eddy New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REPORT, OR OTHER DATA	3465.2' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
	change on Form 9–330.)
MULTIPLE COMPLETE	
ABANDON*	
(other) Drilling Activity	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly staticular including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine	lifectionally utilied, give subsurface locations and
10-15-82: Tripping at 5003', made 453' in last : Bit #4 has made 1942' in 84 1/2 hrs., RPM 60, Wt. on Bit 45,000, M.W. 8.4, was 1 1/4°	24 hrs., drilling at 19' per hrs., Pump Pressure 1200, Strokes 92,
10-16-82: Drilling at 5240', made 237' in last 2 Bit #5, 7 7/8'' Security M89 has made 2 Strokes 92, RPM 60, Wt. on Bit 35,000 at 5017' was 3°, Totco at 5090' was 2	237' in 13 hrs., Pump Pressure 1200, , M.W. 8.4, Vis, 28, PH 9.5, Totco
10-17-82: Drilling at 5596', made 356' in last : Bit #5 has made 593' in 36 3/4 hrs., I RPM 60, Wt. on Bit 35,000, M.W. 8.4, 2 1/2°	Pump Pressure 1200, Strokes 92, Vis. 28, PH 9.5, Totco at 5433' was
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
(This spice for Federal or State o	P*
(ORIG. SGD.) DAVID R. GLASS	DATE
CONDITIONS OF APPROVA DE LA STARE 5 1982	
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO	
ROSWELL, NEW MEAICO	a Side