

UNITED STATES MINERAL OIL CONS. COMMISSION  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
Roswell, NM 88210

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Chama Petroleum Company

3. ADDRESS OF OPERATOR

5447 Glen Lakes Dr., Dallas, Texas 75231

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1650' FNL & 1980' FEL of Sec. 3

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Completion

5. LEASE

NM-14758

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Huber Federal

9. WELL NO.

#2

10. FIELD OR WILDCAT NAME

Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3, T-20-S, R-25-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3465.2' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
OCT 17 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-2-82

thru Waiting on Completion

12-6-82

12-7-82: Moved in & rigged up pulling unit, cut off casing, installed well head & BOP, tripped in hole with 3 7/8" bit and casing scraper on 2 3/8" N-80 tubing, ran 189 joints, shut down overnight.

12-8-82: Finished tripping in hole, top of cement at 9626' by pipe tally, displaced hole with KCL water, rigged up GeoVann, ran Gamma Ray Cased Hole Collar Log from PBDT (9616' by wireline) to 5800', shut down overnight.

12-9-82: Rigged up GeoVann, tied into PDC log, perforated with 4 holes per ft. at 9531 and 9541 with casing gun, rigged down wireline, picked up Vann System

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL \_\_\_\_\_

JAN 18 1983

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

MINERALS MANAGEMENT SERVICE  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side