

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer DD
Artesia, NM 88210

5. LEASE
NM 14118
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Allison CQ Federal
9. WELL NO.
8
10. FIELD OR WILDCAT NAME
Boyd Morrow
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Unit 1, Sec. 14-T19S-R24E
12. COUNTY OR PARISH 13. STATE
Eddy NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD):
3662' GR

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-1 for such proposals.

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980 FSL & 990 FEL, Sec. 14-19S-24E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) ☐ ☐

(NOTE: Report results of multiple completion or zone change on Form 9-331.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
Spudded 17-1/2" hole 8:00 AM 9-8-82. Ran 9 jts of 13-3/8" 48# J-55 casing; set 335'. 1-Texas Pattern notched guide shoe set 335'. Flapper float at 302'. Cemented w/325 sacks Class "C" 3% CaCl₂. Compressive strength of cement - 1275 psi in 12 hours. PD 6:30 PM 9-8-82. Bumped plug to 800 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. WOC. Drilled out 6:30 AM 9-9-82. WOC 12 hours. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineering Secty DATE 9-14-82

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
A.R.I.
OCT 4 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

TITLE

DATE

RECEIVED

See Instructions on Reverse Side

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO