

C/SF

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
2. NAME OF OPERATOR ☒ JAN 14 1983
Exxon Corporation
3. ADDRESS OF OPERATOR O. C. D.
P. O. Box 1600, Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL and 660' FEL of Section
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM - 31200
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Lakewood Federal
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Wildcat Undeveloped
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 34, T19S, R37E
12. COUNTY OR PARISH
Eddy
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to 3650' TD.
Ran 80 jts 5 1/2" 14# K-55 csg set 3644'. Cmt w/300 sx C1 C wt 12.5#, tailed w/350 sx C1 C, 14.8# NEAT.
Did not bump plug. Job complete 9:30 a.m. 12-1-82. WOC
Tested 5 1/2" csg 12-7-82 w/3000#. Held ok
Preparing to perf.

* Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED 4/1/83 TITLE Sr. Administrator DATE December 14, 1982

APPROVED BY _____
CONDITIONS OF APPROVAL _____
ACCEPTED FOR RECORD (This space for Federal or State office use)
JAN 19 1983
MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO