Form 9-331 (May 1983)]		ITED STATE	INTERI	SUBMIT IN A LICATE (Other instructions on r OR verse side)	<u> </u>	orm approved. udget Bureau N BBIGNATION AND	
	RY NOT	CES AND REP als to drill or to deepe TION FOR PERMIT-	ORTS C	ON WELLS ack to a different reservoir.	6. IF INDIA	AN, ALLOTTER OR	TRIRE WAYE
1. OIL GAN WELL WELL] OTHER			RECEIVE	D 7. UNIT AG	ABEMANT NAME	
2. NAME OF OPERATOR		······································		JUL 1 5 19	8. FARM 0	R LBASE NAME	
8. ADDRESS OF OPBRATOR				9. WELL NO.			
		only and in accordance		O. C. D. State requiremental STA, OFFIC		AND POOL, OR WI	TRAN
Bee also space 17 below. At surface					11. BBC., 1	., R., M., OR REK. VBY OR ARRA	÷ .
14. PERMIT NO.		15. BLEVATIONS (Show	whether DF,	. RT, GR, etc.)	12. COUNT	Y OR PARISH 18	. STAEB
16.	Check As	propriate Box To I	ndicate N	ature of Notice, Report, or	Other Date	L I	·····
NOT	FICE OF INTEN	• •			QUENT REPORT		
TEST WATER SHUT-OFF Fracture treat		ULL OR ALTER CARING Aultiple complete		WATER SHUT-OFF		REPAIRING WELL ALTERING CARIN	
HOOT OR ACIDIZE	+	BANDON [®]		#HOOTING OR ACIDIZING		ABANDON MBNT ⁶	·
REPAIR WELL (Other)	L (HANGE PLANS		(Other) (Norm: Report result Completion or Recon	its of multiple	completion on V	Well
<u>4/16/83</u> : Ran sho circ started m Shut down for the 4/18/83: Pulled	e & wash hilling. e day. installa Cagged up	pipe, 4 3 1/2 Returns: ru tion - shoe 1 @ 11,979' -	" D.C. bber, f ooked g	(total length 7.45 & 2 3/8" tbg. Taggerac sand & metal she ood. Ran 2.75" Bowe o get inside of tbg	ed up @ 1 avings. en spear,	1,980'. 1 Quit makin jars, 4	ng hole. 3½" D.C.
4/19/83: Finishe 2 3/8" tbg. Circ				mule tail & J-slot hout success.	on, on &	off tool,	jars &
2 3/8" tbg. Brol	ke circ.	- started mil	ling or	ncave shoe dressed we have shoe dressed we have $1_2'$ - milled $1_2'$ - mount of rubber. Sh	·2' & pkr		
	install			ıll. Ran new 4.50" rc. – resumed millir	ng on Oti	s W.B. pkr	
$3^{1}2''$ D.C. & 2 3/8'	"tbg.to	o 11,981'. Br ved down hole	28'. I	Drilled & pushed pac	ker to l	2,039.19'.	Picked
$3^{1}2''$ D.C. & 2 3/8'	" tbg. to pkr. mov	ved down hole	28'. I	Drilled & pushed pac	ker to 1	2,039.19'.	Picked
3 ¹ 2" D.C. & 2 3/8 Drilled 1 foot &	" tbg. to pkr. mov	ved down hole	28'. 1	Orilled & pushed pac		2,039.19'.	Picked
3 ¹ 2" D.C. & 2 3/8 Drilled 1 foot & 18. I hereby certify that th	" tbg. to pkr. mor	ved down hole true and correct	28'. 1	Drilled & pushed pac			Picked

.

.

•

•

.

*See Instructions on Reverse Side