

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Co., Division  
811 S. 1st Street  
Artesia, NM 88210-2834

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

clsf

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Nearburg Producing Company

3. Address and Telephone No.

3300 N A t. Bldg. 2, Suite 120, Midland, Texas 79705

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

735' FSL and 660' FWL Sec. 35 T 19S R 25E

5. Lease Designation and Serial No.  
NMNM 91079

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Gulf Federal Com # 1Y

9. API Well No.

30-015-24354

10. Field and Pool, or Exploratory Area

Cemetery Atoka, North

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/21/00 Set CIBP @ 8750'

9/22/00 Circ. well W/mud. Spot 25 sks of cement @ 8750'

9/25/00 Cut & pulled 6026' of 4 1/2 casing.

9/26/00 Spot 35 sks of cement @ 6075'. Tagged TOC @ 5905'

9/26/00 Spot 35 sks of cement @ 4120'-3984'

9/26/00 Spot 44 sks of cement @ 2880'-2713' Tagged @ 2713'

9/27/00 Spot 35 sks of cement @ 405'-270'

9/27/00 Spot 14 sks of cement @ 50'-surf.

Cut off wellhead & anchors 3' BGL. Install dry hole marker. Backfill & clean location.



14. I hereby certify that the foregoing is true and correct

Signed Kim Stewart

Title Regulatory Analyst

Date 10/18/00

(This space for Federal or State office use)

Approved by (ORIG. SGD.) GARY GOURLEY

Title PETROLEUM ENGINEER

Date OCT 19 2000

Conditions of approval, if any: