

NEW MEXICO "O" STATE COM #1/ 11,500/D/ATOKA/DENIA #21/EDDY NM/WI .50/1/
STKD 1980' FNL & 1980' FEL, SEC 12 T19S, R28E
AFE 31619 T-320,000 I-645,000 P-*865716* SPUD 12 NOON 01-16-83
01-17 365/RNNG 13-3/8 CSG/SURF ROCK/365/DRILL SURF-365, CIRC, POH, RU NOW RNNG
13-3/8 CSG/T-1000 I-52,472

NEW MEXICO "O" STATE COM #1/ /2/
01-18 365/NU/SURF ROCK/O/R&C 9 JTS 13-3/8 CSG, CS 365 IF 331, CIRC 1/2 HR, HOWCO CMT
W/450 SXS "C" W/2% CACL, JC 1 PM, FP 250-450, CIRC 125 SXS, CMT HELD AT SURF,
WOC, CUT OFF 13-3/8, NU WELL HEAD/T-25,939 I-61,282

NEW MEXICO "O" STATE COM #1/ /3/
01-19 410/D ANHY & SALT/45/NU WELL HEAD, TEST CSG 1000# 1/2 HR OK, TIH, TEST RAMS
1000# OK, DRILL CMT & PLUG/T-25,939 I-62,838

NEW MEXICO "O" STATE COM #1/ /4/
01-20 970/D RB & SALT/560/GAINED WTR FLOW, APPROX 1/2 BPM AT 940/T-25,939 I-74,880

NEW MEXICO "O" STATE COM #1/ /5/
01-21 1265/D ANHY & SALT/295/LOST PUMP PRESSURE AT 1215, POH, LAY DOWN CRACKED DC,
DRLG W/1/2 BPH WATER FLOW/T-25,939 I-82,429

NEW MEXICO "O" STATE COM #1/ /6/
01-22 1580/D ANHY & SALT/315/NO WTR FLOW ON CONNECTIONS/T-25,939 I-89,264

NEW MEXICO "O" STATE COM #1/ /7/
01-23 1840/TRIP FOR CRACKED DC/ANHY/260/AFTER DOWN 2-1/2 HRS, WAIT ON DC SUB,
WTR FLOW START APPROX 1/2 BPH/T-25,939 I-94,860

NEW MEXICO "O" STATE COM #1/ /8/
01-24 2024/D ANHY/184/DRLG W/1/2 BPH WATER FLOW/T-25,939 I-99,279

NEW MEXICO "O" STATE COM #1/ /9/
01-25 2407/D SD/383/NO WTR FLOW WHILE RNNG DEV SURVEY AT 2367/T-25,939 I-108,344

NEW MEXICO "O" STATE COM #1/ /10/
01-26 2891/D ANHY & SD/484/DRLG W/NO WTR FLOW/T-25,939 I-114,456

NEW MEXICO "O" STATE COM #1/ /11/
01-27 3000/POH TO RUN 8-5/8/SD/109/DRILLED TO 3000 AT 11:45 AM, CIRC 4-1/4 HRS,
POH W/BIT, SCHLUM RAN 2 LOGS FOR BASS ENTERPRISES, RUN IH W/BIT, JC 1 AM, NO WTR
FLOW DURING LOGGING OPERATIONS, CIRC 4-1/4 HRS, MIX GEL SWEEP, NOW POH TO RUN
CSG/T-25,939 I-124,231

NEW MEXICO "O" STATE COM #1/ /12/
01-28 3000/WOC/ANHY & SAND/O/R&C 68 JTS 8-5/8 CS 3000 FC 2954, CIRC & RECIPROCATE
CSG 1-1/4 HR, NO WTR FLOW WHEN SHUT DOWN CIRC, HOWCO CMT THRU SHOE W/1800 SXS
HOWCO LITE W/10# SALT & 1/4# FLOCELE, TAIL W/200 SXS "C" W/2% CACL, JC 9:15 PM,
FP 350-1650, FLOAT HELD, CIRC 603 SXS, AFTER 3/4 HR NOTICED FLOW BACK ON BRADEN
HEAD, WASH BOP, CLOSED 8-5/8 RAMS, WOC 6 HRS, OPEN VALVE ON BRADEN HEAD, CAUGHT
SAMPLE OF SOFT CMT, CLOSE VALVE FOR 2-1/2 ADDN HRS, OPEN VALVE IN BRADEN HEAD,
NO FLOW, SLACK TENSION OFF CSG, CSG DID NOT MOVE, NOW NIPPLING DOWN BOP/T-68,901
I-142,586