

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM 88210

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Bel-Dyn, Inc. Properties

3. ADDRESS OF OPERATOR

P.O. Box 136, Lovington, N.M. 88260

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

RECEIVED

APR 22 1983

OIL & GAS  
MINERALS SECTION  
ROSWELL, NEW MEXICO

5. LEASE  
NM 0560353

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
RECEIVED

7. UNIT AGREEMENT NAME

APR 26 1983

8. FARM OR LEASE NAME

Hale Federal O. C. D.

9. WELL NO.

3

ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME

Shugart- Y. Qn.S.R.Q.C-b

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

1-19S-30E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3518.5 G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 10" hole to 530' (Rustler anhydrite @ 490')

Ran and cemented (circulated) 524', 8 5/8", 24# casing.

Drilled to 655', encountered some brine water.

Squeezed open hole- 520'- 655' with 100 sx. (Denton

Cementing, Artesia)

Drilling out cement, rig broke down.

Moved in rotary (Salazar Bros.) & complete 7 7/8" hole to 3088'.

Ran 3088.5', 5 1/2", 15.50 (new) casing, Howco cemented with 425 sx., did not circulate. April 15, 1983.

Ran temp. survey 4/16. Top cement @ 1300 ft. down.

Prepare to drill out below casing, (Queen) in open hole-completion.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Manager/Operations DATE 4-20-83

ACCEPTED FOR RECORD

(space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS

DATE

CONDITIONS OF APPROVAL APR 25 1983

ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side