

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates, R. Co.</u>			Lease <u>Artesia No. 1</u>		Well # <u>1</u>
Location of Well	Unit <u>L</u>	Section <u>16</u>	Township <u>14</u>	Range <u>27</u>	County <u>Zeddy</u>
Drilling Contractor	<u>Adco</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 7/8</u>	<u>43#</u>	<u>New</u>	<u>350'</u>	<u>Circ</u>
<u>16 1/4</u>	<u>8 7/8</u>	<u>24"</u>	<u>"</u>	<u>1800'</u>	<u>Circ</u>
<u>17 1/2</u>	<u>4 1/2 to 5 1/2</u>	<u>10.5 to 11.6"</u> <u>15.8 to 17"</u>	<u>"</u>	<u>TD</u>	<u>500 SX</u>

Casing Data:

Surface            joints of            inch            # Grade             
(Approved) (Rejected)           

Inspected by            date           

Cementing Program

Size of hole 12 1/4 Size of Casing 9 5/8 Sacks cement required 200

Type of Shoe used Tex-Pac Float collar used In'sert Btm 3 jts welded yes

TD of hole 1808 Set 1813 Feet of 9 5/8 Inch 36 # Grade J-55

New-used csg. @ 1813 with 250 sacks neat cement around shoe  
+ 1220 sax Pace Setter litz additives           

Plug down @ 200 (AM) (PM) Date 5-6-83

Cement circulated yes No. of Sacks 150

Cemented by Weston Witnessed by Bull Weaver

Temp. Survey ran @            (AM) (PM) Date            top cement @           

Casing test @            (AM) (PM) Date           

Method Used            Witnessed by           

Checked for shut off @            (AM) (PM) Date           

Method used            Witnessed by           

Remarks: Last Drilling Break 1710 FT