

Form 9-331

Dec. 1977

Form Approved.

Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 730, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Ltr. P, 990' FSL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) Spudded well ☒

(X)

5. LEASE

NM-56220

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

D.D. Federal 24

8. FARM OR LEASE NAME

AUG 15 1983

9. WELL NO.

1

O. C. D.

10. FIELD OR WILDCAT NAME

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 24, T-19S, R-24

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3577.4' F.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/6/83 Spudded well @ 1:00 P.M. By Young Drilling Company. Drlg. 17 1/2" hole @ 328'.

8/7/83 Nippling up 17 1/2" hole @ 373'. Ran 9 jts H-40, 48#, 13 3/8", 8rd csg (346') Set @ 360'. Float collar @ 315'. Howco cemented w/ 1000 gals flocheck, 100 sxs lite thick set, 1/2# flocele / sx., 5# gilsonite / sx, 4% CaCl, 375 sxs class "C", 2% CaCl. Plug down @ 12:00 noon. No returns. WOC 6 hours, ran temp survey top @ 150', ran 1" tubing to 163' cemented w/ 200 sxs class "C", 4% CaCl, circ 30 sxs 8:30 P.M. Cut off & install wellhead.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Area Superintendent

TITLE Area Superintendent DATE August 10, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 12 1983