

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or re-completing a well in a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660 FSL & 2310 FEL, Sec. 5-19S-27E  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Plugback & Perforate		<input checked="" type="checkbox"/>

5. LEASE NM-30629

6. INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Eastern Shore XM Federal

9. WELL NO. 1

10. FIELD OR WILDCAT NAME  
Undes. Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit 0, Sec. 5-T19S-R27E

12. COUNTY OR PARISH Eddy 13. STATE NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3275' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 10016'. Plugged well back as follows: Spotted 50 sack plug from 9493-9643'.  
Set 75 sack plug with retainer 7845-8005'.

WIH and perforated 7675-7802' w/90 .50" holes as follows: 7675-80' (10 holes-2 SPF); 7686-91' (10 holes-2 SPF); 7696-99' (6 holes-2 SPF); 7752-78' (52 holes-2 SPF); 7788-91' (6 holes-2 SPF); 7799-7802' (6 holes-2 SPF). Well unloaded small amount of fluid and stabilized at 400 psi on 1/2" choke = 2585 mcf/gpd.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Production Supervisor DATE 12-14-83

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL \_\_\_\_\_