

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S. G.S.	
LAND OFFICE	
OPERATION	

OIL CONSERVATION DIV. RECEIVED BY

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

OCT 03 1983

O. C. D.

AREASIA, OFFICE

Form C-103
Revised 10-1

5. Indicate type of lease
State ☐ ☒ ☐
5. State C. & G. Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-11) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER	7. Unit Agreement Name
2. Name of Operator Chama Petroleum Company	8. Term of Lease Name South Boyd
3. Address of Operator P.O. Box 31405, Dallas, Texas 75231	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>27</u> TOWNSHIP <u>19 South</u> RANGE <u>25 East</u> N.M.P.M.	10. Field and Pool, or Wildcat Und. Cemetery Morrow
11. Elevation (Show whether DF, RT, GR, etc.) 3455.7 G.L.	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐ Drilling Activity - 4 1/2" casing	CASING TEST AND CEMENT JOB ☐	

Describe in brief, in detail or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-22-83: Drilling at 9420', made 240' in last 24 hrs.

9-23-83: T.D. 9,555', circulating for logs, made 135' in last 24 hrs.

9-24-83: T.D. 9,555', logging, Survey at 9,555' was 3/4°.

9-25-83: T.D. 9,555', cemented total of 237 jts. (9,551'), (48 jts. (1968') of 4 1/2" OD 8rd. 11.60# N-80 & 189 jts. (7587') of 4 1/2" 8rd. 11.60# J-55), set at 9552' KB, displaced mud out of hole with 3% KCL water with corrosion inhibitor, pumped 500 gal. mud flush ahead of 675 sacks 50/50 pox mix H cement with 5/10 of 1% CFR-2, 1/4# flocele, 4/10 of 1% Hallad 22 & 2% gel, followed with 300 sacks Class H cement containing 4/10 of 1% CFR-2, 5/10 of 1% Hallad 22 & 3% KCL, waited on cement 4 1/2 hrs., had good circulation through out cement job & displaced balance of mud in hole, ran temperature survey which indicated top of cement at 6300' from surface outside of 4 1/2" casing

9-26-83: T.D. 9,555', released rig at 3:00 P.M. New Mexico time.

9-27-83

thru Waiting on Completion

9-30-83

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Kathie CraftTITLE SecretaryDATE Sept. 29, 1983

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: