

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity log run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy	T. Lower Canyon	6984	T. Ojo Alamo	T. Penn. "B"			
T. Salt	T. Strawn Mkr	7495	T. Kirtland-Fruitland	T. Penn. "C"			
B. Salt	T. Atoka	7940	T. Pictured Cliffs	T. Penn. "D"			
T. Yates	T. Miss		T. Cliff House	T. Leadville			
T. 7 Rivers	T. Devonian		T. Menefee	T. Madison			
T. Queen	T. Silurian		T. Point Lookout	T. Elbert			
T. Grayburg	T. Montoya		T. Mancos	T. McCracken			
T. San Andres	T. Simpson		T. Gallup	T. Ignacio Qtzite			
T. Glorieta	T. McKee		Base Greenhorn	T. Granite			
T. Paddock	T. Ellenburger		T. Dakota	T.			
T. Blinebry	T. Gr. Wash		T. Morrison	T.			
T. Tubb	T. Granite		T. Todilto	T.			
T. Drinkard	T. Delaware Sand		T. Entrada	T.			
T. Abo	T. Bone Springs		T. Wingate	T.			
T. Wolfcamp	T. Morrow Clastic	8236	T. Chinle	T.			
T. Rake	T. Chester	8443	T. Permian	T.			
T. Cisco (Bough C)	T.		T. Penn. "A"	T.			

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet	
No. 2, from.....to.....feet	
No. 3, from.....to.....feet	
No. 4, from.....to.....feet	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	676	676	Surface, Anhydrite, Dolo.	5886	6000	114	Shale, Lime, Sand
676	2100	1424	Dolomite	6000	6094	94	Shale, Lime
2100	2620	520	Dolomite, Anhydrite	6094	6400	306	Lime
2620	2770	150	Dolomite, Shale	6400	6884	484	Sand, Shale, Lime
2770	2990	220	Dolomite	6884	8240	1356	Lime, Shale
2990	3380	390	Dolomite, Sd, Shale	8240	8500	260	Sand, Shale, Lime
3380	3630	250	Dolomite				
3630	3860	230	Shale, Dolomite				
3860	4668	808	Dolomite				
4668	4914	246	Dolomite, Lime				
4914	5886	972	Shale, Lime				