STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	✓	
FILE	✓	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	✓	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

RECEIVED BY
MAR 07 1984
O. C. D.
ARTESIA, OFFICE

Indicate Type of Lease: State [X] Fee [ ]

5. State Oil & Gas Lease No.: LG 648

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT —" (FORM C-101) FOR SUCH PROPOSALS.)

7. Unit Agreement Name

OIL WELL [ ] GAS WELL [X] OTHER-

2. Name of Operator: Yates Petroleum Corporation ✓

8. Farm or Lease Name: Millman SB State

3. Address of Operator: 207 South 4th St., Artesia, NM 88210

9. Well No.: 2

4. Location of Well
UNIT LETTER K, 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 19S RANGE 28E NMPM.

10. Field and Pool, or Wildcat: Und. South Millman Morrow

15. Elevation (Show whether DF, RT, GR, etc.): 3499' GR

12. County: Eddy

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK [ ]	PLUG AND ABANDON [ ]	REMEDIAL WORK [ ]	ALTERING CASING [ ]
TEMPORARILY ABANDON [ ]		COMMENCE DRILLING OPNS. [ ]	PLUG AND ABANDONMENT [ ]
PULL OR ALTER CASING [ ]	CHANGE PLANS [ ]	CASING TEST AND CEMENT JOB [ ]	
OTHER [ ]		OTHER Intermediate Casing	[X]

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 60 jts 8-5/8" 32# J-55 ST&C casing set 2588'. Regular guide shoe set 2588'. Super Seal Float collar set 2547'. Cemented w/1750 sacks Howco Lite, 10# salt, 1/4# flocele/sack. Tailed in w/300 sacks Class "C" 2% CaCl2. PD 9:15 AM 2-23-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 45 sacks. WOC. Drilled out 3:00 PM 2-24-84. WOC 29 hrs and 45 minutes. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [signature] TITLE Production Supervisor DATE 3-6-84

APPROVED BY Original Signed By Leslie A. Clements TITLE Supervisor District II DATE MAR 0 8 1984

CONDITIONS OF APPROVAL, IF ANY: