


STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78



5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG 648

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - I" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Millman SB State
3. Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 2
4. Location of Well UNIT LETTER <u>K</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>16</u> TOWNSHIP <u>19S</u> RANGE <u>28E</u> NWMPA.	10. Field and Pool, or Wildcat Und. South Millman Morro
15. Elevation (Show whether DF, RT, GR, etc.) 3499' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Production Casing, Perforate</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11296'. Ran 277 jts of 4-1/2" 11.6# N-80 casing set 11296'. \* Float collar set 11256'. Cemented w/620 sacks Class "H" Poz, 2% gel, 2# KCL, .5% Halad-22A and .3% CFR-2. Tailed in w/310 sacks Class "H", 2% KCL, .5% Halad-22A and .3% CFR-3. Compressive strength of cement - 1050 psi in 12 hrs. PD 3:00 PM 3-23-84. Bumped plug to 1000 psi for 30 minutes, released pressure, float and casing held okay. WOC 18 hrs. WIH and perforated 10966-11015' w/100 .50" holes (4 SPF) as follows: 10966-70', 10975-81', 10990-11000' and 11010-15'. Well flowed 280 psi on 1/2" choke = 1835 mcf/gpd.

Note: \*1-regular guide shoe set 11296'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Production Supervisor DATE 4-4-84  
Original Signed By  
Leslie A. Clements  
Supervisor District II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE APR 18 1984

CONDITIONS OF APPROVAL, IF ANY: