

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

SUBMIT IN TRIPLICATE*
(Other instructions on re-
lease forms.)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 8673

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Benson Deep Unit

8. FARM OR LEASE NAME

Benson Deep Unit

9. WELL NO.

4

10. FIELD AND POOL, OR WINDLIFT
Undes. Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit F, Sec. 3-T19S-R30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3414' GR

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 17-1/2" hole 4:30 AM 3-13-84. Ran 8 joints of 13-3/8" 54.5# J-55 ST&C casing set at 350'. 1-Texas Pattern notched guide shoe set at 350'. Insert float set at 311'. Cemented w/500 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 7:15 PM 3-31-84. Plug did not bump. Shut well in. Cement circulated 50 sacks. WOC. Drilled out at 1:15 PM 4-1-84. WOC 18 hours. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling. Ran 48 joints of 9-5/8" 36# J-55 ST&C casing set at 1900'. 1-Texas Pattern notched guide shoe set at 1900'. Insert float set at 1860'. Cemented w/500 sacks Pacesetter Lite, 10#/sack Hi-seal, 1/4#/sack celloseal and 2% CaCl2. Tailed in w/250 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 10:00 AM 4-3-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Note: Mr. Cove with BLM on location. Drilled out at 10:00 AM 4-4-84. WOC 24 hours. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 8-3/4". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Supervisor

DATE

4-10-84

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

MAY 7 1984